



Shenzhen SMX TECHNOLOGY CO.,LTD



MX-L405X

Resolution XGA up to WUXGA

Brightness 4000 lm

Contrast 20,000:1

Lamp up to 20,000 Hours



Outstanding Performance in a Compact Body

High Brightness, Contrast ratio, display Color

Brightness can reach up to 4000 lumens, This series is completely equipped with 20000:1 ratio, high color display 1.07 Billion . Even in standard daylight classroom & meeting rooms, presentation brightness is guaranteed to deliver vivid moving colors.

Extra Long-life Lamp

High quality long life lamps. These series delivers well engineered lamp type that could last up to 20,000 hours. Effectively reduce extra maintenance cost on lamp replacements.

Super-Fast Start Up and shut down

Zero second Flash start & shut mode kills waiting time and more business matters.

Power-trip protection safety feature

The series comes with short circuit protection feature that anticipate unexpected power cut. Given this ability, it protects expensive components boards and lamp safety.

Vertical – Horizontal Keystone correction

The Keystone correction feature allow image to merge to scale onto any projector screen.

Automatic picture correction feature

Auto sensing feature allow ceiling hanged projector to auto flipped a direct display. It provide no setup or any prior installation knowledge.

Multiple inputs feature

2 * sets HDMI, 1 * sets VGA inputs, USB – A USB-B, VIDEO input. Across all format and platforms, users of any setup can install with ease.

USB Reader, Wireless connectivity

With a USB-A input, can read the data from the USB disk directly, USB-B support wireless connection with projection equipment.

Quick snap lamp & Filter replacement design

Design with ceiling installation in mind, projector Users without much training could replace the lamp or filter in a snap. Maintenance can be more regular and with ease by any facility officers.

Remote Access Health Check

Through RJ45 Internet access, you could get access to your projector. Projector allows status notifications in any unexpected events. It is ready to send an email to notify you of any maintenance care it required.

Compatibility Support

Projectors is built to mix with its class of equipment. It support PJLINK, CRESTRON-ROOMVIEW, and AMX-DISCOVERY via internet command systems. Its blends into system and work seamlessly with other brands projectors.

ESD Anti Dusting feature

Equipped with high efficient electrostatic dusting functions within the projector, it keeps the LCDs and lenses dust free from any environment.



Shenzhen SMX TECHNOLOGY CO.,LTD

Specification

Model	MX-L405X	
Display Technology	(Liquid Crystal Display) LCD panel (x 3, R/G/B)	
LCD Panels	SONY 3*0.63	
Brightness	4000 lumens	
Resolution	XGA (1024*768)	
Contrast	20000:1	
Lens	F1.6~1.76, f=19.158~23.018mm (1.2x) optical zoom	
Uniformity	90%	
Throw ratio	1.48~1.78:1 (70" @ 2.1m)	
Aspect ratio	4:3 support 16:9	
Projection distance	0.90m~11m	
Projection size	30:300 inch	
Lamp power	225w	
Lamp life	Normal 10000 hrs. Economic 20000 hrs.	
Input	2*HDMI1.4, 1-VGA, 1*Audio 3.5 Mini-Jack 1*Video, USB-A (Support memory viewer/optional Wi-Fi dongle) 2-Audio-In (L/R), USB-B (Display), RJ45 (Display)	
Output	VGA , Audio 3.5 Mini-Jack	
Control	RS232, RJ45 (control), USB-B (display)	
PC Compatibility	VGA, SVGA, XGA, SXGA, WXGA, UXGA, WUXGA, Mac	
Video Compatibility	PAL, SECAM, NTSC 4.43, PAL-M, PAL-N, 480i, 480p, 576i, 576p, 720p, 1080p and 1080i	
Scanning Frequency	H: 15~100Khz , V: 48~85Hz	
Keystone correction	V. ±30° (Auto/Manual) H. ±30° (Manual), Pincushion/Barrel Correction, Corner Keystone	
Noise	35 dB (lamp control: Normal), 30 dB (lamp control: Eco)	
Projection	Front, Rear, Desktop, Ceiling	
Speakers	10W*1	
Power Consumption	217 Watts	
Power Supply	100V - 240V @ 50 - 60Hz	
Operating Temp.	0°C - 40°C (Over 35°C Go to ECO Mode)	
Storage Temp.	-10°C - 55°C	
OSD Languages	26 languages: English, German, French, Italian, Spanish, Polish, Swedish, Dutch ,Portuguese, Japanese, Simplified Chinese, Traditional Chinese, Korean, Russian, Arabic, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian, Czech, Kazak, Vietnamese, Thai, Persian	
Dimensions	34.5cm x 26.1cm x 9.9cm	
Weight	3.26Kg	
Standard Accessories	Power Cord, Remote Control, VGA Cable	
Optional accessories	Replacement lamp module, Wi-Fi display module, HDMI cable, Screen, Bracket	
Other Features	One Touch Lamp Replacement Quick Power OFF Customized Startup Logo Auto Image Reverse Build in Test Images Corner Keystone	Powerful 10 Watts Speaker HDMI Compatible with MHL LAN Display PC Less Presentation Mirror Display with iOS/Android Devices Via USB Adapter Color display 1.07 Billion



SMX

Shenzhen SMX TECHNOLOGY CO., LTD

www.smxdisplay.com

